


CODO 45° RADIO CORTO
SCH 80


Conforme a:
 ASME B16.9 - ASME 16.28
 ASTM A-234

Diámetro Nominal		Identificación		Diámetro Externo (OD)		Diámetro Interno (ID)		espesor de pared (T)		Avance (A)		Peso nominal	
(NPS)	DN	Weight Class	Schedule N°	mm	inch	mm	inch	mm	inch	mm	inch	Lb	Kg
3"	80	XS	80	88.90	3.50	73.66	2.90	7.6	0.30	50.8	2.000	3.30	1.50
4"	100	XS	80	114.30	4.50	97.18	3.83	8.6	0.34	63.5	2.500	6.20	2.81
5"	125	XS	80	141.30	5.56	122.25	4.81	9.5	0.38	79.2	3.120	10.50	4.76
6"	150	XS	80	168.28	6.63	146.33	5.76	11.0	0.43	95.3	3.75	17.00	7.71
8"	200	XS	80	219.08	8.63	193.68	7.63	12.7	0.50	127.0	5.00	34.30	15.56
10"	250	-	80	273.05	10.75	242.87	9.56	15.1	0.59	158.8	6.25	55.00	24.95
12"	300	-	80	323.85	12.75	288.90	11.37	17.5	0.69	190.5	7.50	80.00	36.29