


**CODO 45° RADIO LARGO
 SCH 40 y STD**

 Conforme a:
 ASME B16.9 y ASTM A-

Diámetro Nominal		Identificación		Diámetro Externo (OD)		Diámetro Interno (ID)		espesor de pared (T)		Avance (A)		Peso nominal	
(NPS)	DN	Weight Class	Schedule N°	mm	inch	mm	inch	mm	inch	mm	inch	Lb	Kg
1/2"	15	STD	40	21.3	0.84	15.80	0.62	2.8	0.109	15.7	0.62	0.09	0.04
3/4"	20	STD	40	26.7	1.05	20.9	0.82	2.9	0.113	19.1	0.75	0.10	0.05
1"	25	STD	40	33.4	1.32	26.6	1.05	3.4	0.133	22.4	0.88	0.22	0.10
1-1/4"	32	STD	40	42.2	1.66	35.1	1.38	3.6	0.140	25.4	1.00	0.33	0.15
1-1/2"	40	STD	40	48.3	1.90	40.9	1.61	3.7	0.145	28.4	1.12	0.43	0.20
2"	50	STD	40	60.3	2.38	52.5	2.07	3.9	0.154	35.1	1.38	0.85	0.39
2-1/2"	65	STD	40	73.0	2.88	62.7	2.47	5.2	0.203	44.5	1.75	1.70	0.77
3"	80	STD	40	88.9	3.5	77.9	3.1	5.5	0.216	50.8	2.00	2.50	1.13
4"	100	STD	40	114.3	4.5	102.3	4.0	6.0	0.237	63.5	2.50	4.50	2.04
5"	125	STD	40	141.3	5.6	128.2	5.0	6.6	0.258	79.2	3.12	7.5	3.4
6"	150	STD	40	168.3	6.6	154.1	6.1	7.1	0.280	95.3	3.75	11.7	5.3
8"	200	STD	40	219.1	8.6	202.7	8.0	8.2	0.322	127.0	5.00	23.3	10.6
10"	250	STD	40	273.1	10.8	254.5	10.0	9.3	0.365	158.8	6.25	40.9	18.6
12"	300	STD	40	323.9	12.8	304.8	12.0	9.5	0.375	190.5	7.50	65.0	29.5
14"	350	STD	30	355.6	14.0	336.6	13.3	9.5	0.375	222.3	8.75	78.1	35.4
16"	400	STD	30	406.4	16.0	387.4	15.3	9.5	0.375	254.0	10.00	101.0	45.8
18"	450	STD	-	457.2	18.0	438.2	17.3	9.5	0.375	285.8	11.25	128.0	58.1
20"	500	STD	20	508.0	20.0	489.0	19.3	9.53	0.375	317.5	12.50	159.0	72.1
24"	600	STD	20	609.6	24.0	590.6	23.3	9.53	0.375	381.0	15.00	231.0	104.8
30"	750	STD	-	762.0	30.0	743.0	29.3	9.53	0.375	469.9	18.50	358.0	162.4
36"	900	STD	-	914.4	36.0	895.4	35.3	9.53	0.375	565.2	22.25	518.0	235.0