


CODO 45° RADIO LARGO

SCH 80 y XS



Conforme a:
 ASME B16.9 y ASTM A-234

Diámetro Nominal		Identificación		Diámetro Externo (OD)		Diámetro Interno (ID)		espesor de pared (T)		Avance (A)		Peso nominal	
(NPS)	DN	Weight Class	Schedule N°	mm	inch	mm	inch	mm	inch	mm	inch	Lb	Kg
1/2"	15	XS	80	21.34	0.840	13.87	0.546	3.7	0.147	15.7	0.620	0.15	0.07
3/4"	20	XS	80	26.67	1.050	18.85	0.742	5.6	0.219	19.1	0.750	0.16	0.07
1"	25	XS	80	33.40	1.315	24.31	0.957	4.5	0.179	20.3	0.800	0.28	0.13
1-1/4"	32	XS	80	42.16	1.660	32.46	1.278	4.9	0.191	25.4	1.000	0.45	0.20
1-1/2"	40	XS	80	48.26	1.900	38.10	1.500	5.1	0.200	28.4	1.120	0.61	0.28
2"	50	XS	80	60.33	2.375	49.25	1.939	5.5	0.218	35.1	1.380	1.20	0.54
2-1/2"	65	XS	80	73.03	2.875	59.00	2.323	7.0	0.276	44.5	1.750	2.00	0.91
3"	80	XS	80	88.90	3.50	73.66	2.90	7.6	0.30	50.8	2.000	3.30	1.50
4"	100	XS	80	114.30	4.50	97.18	3.83	8.6	0.34	63.5	2.500	6.20	2.81
5"	125	XS	80	141.30	5.56	122.25	4.81	9.5	0.38	79.2	3.120	10.50	4.76
6"	150	XS	80	168.28	6.63	146.33	5.76	11.0	0.43	95.3	3.75	17.00	7.71
8"	200	XS	80	219.08	8.63	193.68	7.63	12.7	0.50	127.0	5.00	34.30	15.56
10"	250	-	80	273.05	10.75	242.87	9.56	15.1	0.59	158.8	6.25	55.00	24.95
12"	300	-	80	323.85	12.75	288.90	11.37	17.5	0.69	190.5	7.50	80.00	36.29
14"	350	XS	-	355.60	14.00	330.20	13.00	12.7	0.50	222.3	8.75	100.00	45.36
16"	400	XS	40	406.40	16.00	381.00	15.00	12.7	0.50	254.0	10.00	134.00	60.78
18"	450	XS	-	457.20	18.00	431.80	17.00	12.7	0.50	285.8	11.25	170.00	77.11
20"	500	XS	40	508.00	20.00	482.60	19.00	12.70	0.50	317.50	12.50	209.00	94.80