


CLASS 3000
CODO 90° SOCKET-WELD

 Conforme a:
 ASME B16.11 y ASTM A-105

Diámetro Nominal		Rating pressure	Diámetro Interno Socked		Diámetro Interno Fitting		Espesor pared Socked		Espesor de pared fitting		altura de Socked (min)		Centro a fondo de Socked		Peso nominal	
(NPS)	DN		Class	(B) [Nota 1]		(D) [Nota 1]		(C)		(G)		(J)		(A)		Aprox
				mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	Lb
1/2"	15	3000	22.2	0.87	16.6	0.65	4.67	0.18	3.73	0.147	9.5	0.37	15.5	0.61	0.48	0.22
			21.8	0.86	15.0	0.59										
3/4"	20	3000	27.6	1.09	21.7	0.9	4.90	0.19	3.91	0.154	12.5	0.49	19.0	0.75	0.68	0.31
			27.2	1.07	20.2	0.8										
1"	25	3000	34.3	1.35	27.4	1.08	5.69	0.22	4.55	0.179	12.5	0.49	22.5	0.89	1.06	0.48
			33.9	1.33	25.9	1.02										
1-1/4"	32	3000	43.1	1.70	35.8	1.4	6.07	0.24	4.85	0.191	12.5	0.49	27.0	1.06	1.72	0.78
			42.7	1.68	34.3	1.4										
1-1/2"	40	3000	49.2	1.94	41.6	1.64	6.35	0.25	5.08	0.200	12.5	0.49	32.0	1.26	2.33	1.06
			48.8	1.92	40.1	1.58										
2"	50	3000	61.7	2.43	53.3	2.1	6.93	0.27	5.54	0.218	16.0	0.63	38.0	1.50	3.88	1.76
			61.2	2.41	51.7	2.0										
2-1/2"	65	3000	74.4	2.93	64.2	2.53	8.76	0.34	7.01	0.276	16.0	0.63	41.0	1.61	7.34	3.33
			73.9	2.91	61.2	2.41										
3"	80	3000	90.3	3.56	79.4	3.1	9.52	0.37	7.62	0.300	16.0	0.63	57.0	2.24	11.61	5.27
			89.8	3.54	76.4	3.0										
4"	100	3000	115.7	4.56	103.8	4.09	10.69	0.42	8.56	0.337	19.0	0.75	66.5	2.62	22.47	10.19
			115.2	4.54	100.7	3.96										

Nota:

1) Valores mínimos y máximos de las dimensiones indicadas