


**CODO 90° RADIO CORTO
 SCH 80**

 Conforme a:
 ASME B16.9 y ASTM A-234

Diámetro Nominal		Identificación		Diámetro Externo (OD)		Diámetro Interno (ID)		espesor de pared (T)		Avance (C)		Peso nominal	
(NPS)	DN	Weight Class	Schedule N°	mm	inch	mm	inch	mm	inch	mm	inch	Lb	Kg
1"	25	XS	80	33.4	1.315	24.3	0.957	4.5	0.179	25.4	1.00	0.30	0.14
1-1/4"	32	XS	80	42.2	1.660	32.5	1.278	4.9	0.191	31.8	1.25	0.60	0.27
1-1/2"	40	XS	80	48.3	1.900	38.1	1.500	5.1	0.200	38.1	1.50	0.80	0.36
2"	50	XS	80	60.3	2.375	49.3	1.939	5.5	0.218	50.8	2.00	1.50	0.68
2-1/2"	65	XS	80	73.0	2.875	59.0	2.323	7.0	0.276	63.5	2.50	2.60	1.18
3"	80	XS	80	88.9	3.500	73.7	2.900	7.6	0.300	76.2	3.00	3.80	1.72
4"	100	XS	80	114.3	4.500	97.2	3.826	8.6	0.337	101.6	4.00	7.60	3.45
5"	125	XS	80	141.3	5.563	122.3	4.813	9.5	0.375	127.0	5.00	13.80	6.26
6"	150	XS	80	168.3	6.625	146.3	5.761	11.0	0.432	152.4	6.00	22.80	10.34
8"	200	XS	80	219.1	8.625	193.7	7.625	12.7	0.500	203.2	8.00	47.30	21.45
10"	250	-	80	273.1	10.750	242.9	9.562	15.1	0.594	254.0	10.0	75.00	34.02
12"	300	STD	-	323.9	12.750	304.8	12.000	9.5	0.375	304.8	12.0	79.40	36.02
12"	300	XS	-	323.9	12.750	242.9	9.562	15.1	0.594	254.0	10.0	104.00	47.17