


Aceros – Válvulas – Tuberías y Accesorios – Sistemas Contra Incendio

CODO 90° RADIO LARGO
SCH 40 y STD



Conforme a:
ASME B16.9 y ASTM A-234

Diámetro Nominal		Identificación		Diámetro Externo (OD)		Diámetro Interno (ID)		espesor de pared (T)		Avance (C)		Peso nominal	
(NPS)	DN	Weight Class	Schedule N°	mm	inch	mm	inch	mm	inch	mm	inch	Lb	Kg
1/2"	15	STD	40	21.3	0.84	15.80	0.62	2.8	0.109	38.1	1.50	0.16	0.07
3/4"	20	STD	40	26.7	1.05	20.9	0.82	2.9	0.113	38.1	1.50	0.17	0.08
1"	25	STD	40	33.4	1.32	26.6	1.05	3.4	0.133	38.1	1.50	0.40	0.18
1-1/4"	32	STD	40	42.2	1.66	35.1	1.38	3.6	0.140	47.8	1.88	0.55	0.25
1-1/2"	40	STD	40	48.3	1.90	40.9	1.61	3.7	0.145	57.2	2.25	0.80	0.36
2"	50	STD	40	60.3	2.38	52.5	2.07	3.9	0.154	76.2	3.00	1.60	0.73
2-1/2"	65	STD	40	73.0	2.88	62.7	2.47	5.2	0.203	95.3	3.75	3.20	1.45
3"	80	STD	40	88.9	3.5	77.9	3.1	5.5	0.216	114.3	4.5	4.80	2.18
4"	100	STD	40	114.3	4.5	102.3	4.0	6.0	0.237	152.4	6.0	8.90	4.04
5"	125	STD	40	141.3	5.6	128.2	5.0	6.6	0.258	190.5	7.5	15.1	6.8
6"	150	STD	40	168.3	6.6	154.1	6.1	7.1	0.280	228.6	9.0	24.0	10.9
8"	200	STD	40	219.1	8.6	202.7	8.0	8.2	0.322	304.8	12.0	47.8	21.7
10"	250	STD	40	273.1	10.8	254.5	10.0	9.3	0.365	381.0	15.0	83.4	37.8
12"	300	STD	-	323.9	12.8	304.8	12.0	9.5	0.375	457.2	18.0	123.0	55.8
14"	350	STD	30	355.6	14.0	336.6	13.3	9.5	0.375	533.4	21.0	155.5	70.5
16"	400	STD	30	406.4	16.0	387.4	15.3	9.5	0.375	609.6	24.0	206.0	93.4
18"	450	STD	-	457.2	18.0	438.2	17.3	9.5	0.375	685.8	27.0	262.0	118.8
20"	500	STD	20	508.0	20.0	489.0	19.3	9.53	0.375	762.0	30.0	324.0	147.0
24"	600	STD	20	609.6	24.0	590.6	23.3	9.53	0.375	914.4	36.0	466.0	211.4
30"	750	STD	-	762.0	30.0	743.0	29.3	9.53	0.375	1143.0	45.0	720.0	326.6
36"	900	STD	-	914.4	36.0	895.4	35.3	9.53	0.375	1371.6	54.0	1039.0	471.3