


Aceros – Válvulas – Tuberías y Accesorios – Sistemas Contra Incendio

**CLASS 3000**
**COUPLING ROSCADO**

 Conforme a:  
 ASME B16.11 y ASTM A-105

**COUPLING CLASS 3000 CON ROSCA**

Diámetro Nominal		Rating pressure	Diámetro Externo		Espesor de pared		Longitud		Long de Rosca (min)		Peso nominal	
(NPS)	DN	Class	mm	inch	mm	inch	mm	inch	mm	inch	Lb	Kg
1/4"	8	3000	19.0	0.75	4.80	0.189	35.0	1.38	10.20	0.40	0.10	0.05
3/8"	10	3000	22.0	0.87	4.80	0.189	38.0	1.50	10.40	0.41	0.13	0.08
1/2"	15	3000	28.0	1.10	6.40	0.252	48.0	1.89	13.60	0.54	0.28	0.13
3/4"	20	3000	35.0	1.38	6.40	0.252	51.0	2.01	13.90	0.55	0.44	0.20
1"	25	3000	44.0	1.73	9.70	0.382	60.0	2.36	17.30	0.68	1.08	0.49
1-1/4"	32	3000	57.0	2.24	9.70	0.382	67.0	2.64	18.00	0.71	1.68	0.76
1-1/2"	40	3000	64.0	2.52	11.20	0.441	79.0	3.11	18.40	0.72	2.17	0.98
2"	50	3000	76.0	2.99	12.70	0.500	86.0	3.39	19.20	0.76	3.20	1.45
2-1/2"	65	3000	92.0	3.62	15.70	0.618	92.0	3.62	28.90	1.14	4.70	2.13
3"	80	3000	108.0	4.25	19.00	0.748	108.0	4.25	30.50	1.20	6.80	3.08
4"	100	3000	140.0	5.51	22.40	0.882	121.0	4.76	33.00	1.30	12.30	5.58