


Aceros – Válvulas – Tuberías y Accesorios – Sistemas Contra Incendio

CLASS 3000
COUPLING REDUCTOR

 Conforme a:
 ASME B16.11 y ASTM A-105

COUPLING REDUCTOR CLASS 3000 CON ROSCA												
Diámetro Nominal		Rating pressure	Longitud		Diámetro Externo		Long de Rosca (min)		Long de Rosca (min)		Peso nominal	
(NPS)	DN	Class	(A)		(B)		(L1)		(L2)		Aprox	
			mm	inch	mm	inch	mm	inch	mm	inch	Lb	Kg
3/8 X 1/4	10 X 8	3000	38.0	1.50	22.0	0.87	10.4	0.41	10.20	0.40	0.20	0.08
1/2 X 1/4	15 X 8	3000	48.0	1.89	28.0	1.10	13.6	0.54	10.20	0.40	0.85	0.39
1/2 X 3/8	15 X 10	3000	48.0	1.89	28.0	1.10	13.6	0.54	10.40	0.41	0.78	0.35
3/4 X 1/2	20 X 15	3000	51.0	2.01	35.0	1.38	13.9	0.55	13.60	0.54	1.16	0.53
1 X 1/2	25 X 15	3000	60.0	2.36	44.0	1.73	17.3	0.68	13.60	0.54	1.85	0.84
1 X 3/4	25 X 15	3000	60.0	2.36	44.0	1.73	17.3	0.68	13.90	0.55	1.73	0.78
1-1/4 X 3/4	32 X 20	3000	67.0	2.64	57.0	2.24	18.0	0.71	13.90	0.55	2.60	1.18
1-1/4 X 1	32 X 20	3000	67.0	2.64	57.0	2.24	18.0	0.71	17.30	0.68	2.55	1.16
1-1/2 X 3/4	40 X 20	3000	79.0	3.11	64.0	2.52	18.4	0.72	13.90	0.55	4.70	2.13
1-1/2 X 1	40 X 25	3000	79.0	3.11	64.0	2.52	18.4	0.72	17.30	0.68	4.59	2.08
1-1/2 X 1-1/4	40 X 32	3000	79.0	3.11	64.0	2.52	18.4	0.72	18.00	0.71	4.45	2.02
2 X 1	50 X 25	3000	86.0	3.39	76.0	2.99	19.2	0.76	17.30	0.68	7.40	3.36
2 X 1-1/4	50 X 32	3000	86.0	3.39	76.0	2.99	19.2	0.76	18.00	0.71	7.20	3.27
2 X 1-1/2	50 X 40	3000	86.0	3.39	76.0	2.99	19.2	0.76	18.40	0.72	7.05	3.20
2-1/2 X 1-1/2	65 X 40	3000	92.0	3.62	92.0	3.62	28.9	1.14	18.40	0.72	9.05	4.11
2-1/2 X 2	65 X 50	3000	92.0	3.62	92.0	3.62	28.9	1.14	19.20	0.76	8.62	3.91
3 X 2	80 X 50	3000	108.0	4.25	108.0	4.25	30.5	1.20	19.20	0.76	10.10	4.58
4 x 3	100 X 80	3000	121.0	4.76	140.0	5.51	33.0	1.30	30.50	1.20	12.42	5.63