


Aceros – Válvulas – Tuberías y Accesorios – Sistemas contra incendio

CLASS 150
• COUPLING REDUCTOR


| NPS | DN | Peso Aprox | | Ancho del Reborde (min) | | Espesor de pared (min) | | Diámetro externo del reborde (min) | | Rib | | Longitud | |
|---------------|---------|------------|------|-------------------------|-------|------------------------|-------|------------------------------------|-------|-----|-------|----------|-------|
| | | | | E | | G | | H | | | | M | |
| | | Kg | Lbs | mm | pulg. | mm | pulg. | mm | pulg. | mm | pulg. | mm | pulg. |
| 3/8 X 1/4 | 10 X 8 | 0.05 | 0.11 | 5.8 | 0.23 | 2.5 | 0.10 | 25.8 | 1.02 | 2.5 | 0.10 | 28.7 | 1.13 |
| 1/2 X 1/4 | 15 X 8 | 0.07 | 0.15 | 6.3 | 0.25 | 2.7 | 0.11 | 30.4 | 1.20 | 2.7 | 0.11 | 31.8 | 1.25 |
| 1/2 X 3/8 | 15 X 10 | 0.08 | 0.18 | 6.3 | 0.25 | 2.7 | 0.11 | 30.4 | 1.20 | 2.7 | 0.11 | 31.8 | 1.25 |
| 3/4 X 1/4 | 20 X 8 | 0.10 | 0.22 | 6.9 | 0.27 | 3.0 | 0.12 | 37.1 | 1.46 | 3.0 | 0.12 | 36.58 | 1.44 |
| 3/4 X 3/8 | 20 X 10 | 0.11 | 0.24 | 6.9 | 0.27 | 3.1 | 0.12 | 37.0 | 1.46 | 3.1 | 0.12 | 36.6 | 1.44 |
| 3/4 X 1/2 | 20 X 15 | 0.12 | 0.26 | 6.9 | 0.27 | 3.1 | 0.12 | 37.0 | 1.46 | 3.1 | 0.12 | 36.6 | 1.44 |
| 1 X 1/2 | 25 X 15 | 0.18 | 0.40 | 7.7 | 0.30 | 3.4 | 0.13 | 45.0 | 1.77 | 3.4 | 0.13 | 42.9 | 1.69 |
| 1 X 3/4 | 25 X 20 | 0.20 | 0.44 | 7.7 | 0.30 | 3.4 | 0.13 | 45.0 | 1.77 | 3.4 | 0.13 | 42.9 | 1.69 |
| 1-1/4 X 1/2 | 32 X 15 | 0.28 | 0.62 | 8.7 | 0.34 | 3.7 | 0.14 | 54.7 | 2.15 | 3.6 | 0.14 | 52.3 | 2.06 |
| 1-1/4 X 3/4 | 32 X 20 | 0.29 | 0.64 | 8.7 | 0.34 | 3.7 | 0.14 | 54.7 | 2.15 | 3.6 | 0.14 | 52.3 | 2.06 |
| 1-1/4 X 1 | 32 X 25 | 0.31 | 0.68 | 8.7 | 0.34 | 3.7 | 0.14 | 54.7 | 2.15 | 3.6 | 0.14 | 52.3 | 2.06 |
| 1-1/2 X 1/2 | 40 X 15 | 0.35 | 0.77 | 9.3 | 0.37 | 3.9 | 0.16 | 61.6 | 2.43 | 3.8 | 0.15 | 58.7 | 2.31 |
| 1-1/2 X 3/4 | 40 X 20 | 0.40 | 0.88 | 9.3 | 0.37 | 3.9 | 0.16 | 61.6 | 2.43 | 3.8 | 0.15 | 58.7 | 2.31 |
| 1-1/2 X 1 | 40 X 25 | 0.41 | 0.90 | 9.3 | 0.37 | 3.9 | 0.16 | 61.6 | 2.43 | 3.8 | 0.15 | 58.7 | 2.31 |
| 1-1/2 X 1-1/4 | 40 X 32 | 0.42 | 0.93 | 9.3 | 0.37 | 3.9 | 0.16 | 61.6 | 2.43 | 3.8 | 0.15 | 58.7 | 2.31 |
| 2 X 1/2 | 50 X 15 | 0.59 | 1.30 | 10.7 | 0.42 | 4.4 | 0.17 | 75.3 | 2.96 | 4.4 | 0.17 | 71.4 | 2.81 |
| 2 X 3/4 | 50 X 20 | 0.61 | 1.34 | 10.7 | 0.42 | 4.4 | 0.17 | 75.3 | 2.96 | 4.4 | 0.17 | 71.4 | 2.81 |
| 2 X 1 | 50 X 25 | 0.63 | 1.39 | 10.7 | 0.42 | 4.4 | 0.17 | 75.3 | 2.96 | 4.4 | 0.17 | 71.4 | 2.81 |
| 2 X 1-1/4 | 50 X 32 | 0.69 | 1.52 | 10.7 | 0.42 | 4.4 | 0.17 | 75.3 | 2.96 | 4.4 | 0.17 | 71.4 | 2.81 |
| 2 X 1-1/2 | 50 X 40 | 0.70 | 1.54 | 10.7 | 0.42 | 4.4 | 0.17 | 75.3 | 2.96 | 4.4 | 0.17 | 71.4 | 2.81 |

Conforme a:

MSS-SP-114 / ASME B16.3 - ASTM A-351 - ASME B1.20.1 (Rosca NPT)