


Aceros – Válvulas – Tuberías y Accesorios – Sistemas Contra Incendio

CLASS 3000
TAPON HEMBRA (CAP) ROSCADO

Conforme a:
 ASME B16.11 y ASTM A-105

TAPON HEMBRA CLASS 3000 CON ROSCA												
Diámetro Nominal		Rating pressure	Diámetro Externo		Espesor de pared		Longitud		Long de Rosca (min)		Peso nominal	
(NPS)	DN		(D)		(G)		(P)		(L2)		Aprox	
		Class	mm	inch	mm	inch	mm	inch	mm	inch	Lb	Kg
1/4"	8	3000	19.0	0.75	4.80	0.189	25.0	0.98	10.20	0.40	0.08	0.04
3/8"	10	3000	22.0	0.87	4.80	0.189	25.0	0.98	10.40	0.41	0.11	0.05
1/2"	15	3000	28.0	1.10	6.40	0.252	32.0	1.26	13.60	0.54	0.23	0.10
3/4"	20	3000	35.0	1.38	6.40	0.252	37.0	1.46	13.90	0.55	0.40	0.18
1"	25	3000	44.0	1.73	9.70	0.382	41.0	1.61	17.30	0.68	0.79	0.36
1-1/4"	32	3000	57.0	2.24	9.70	0.382	44.0	1.73	18.00	0.71	1.21	0.55
1-1/2"	40	3000	64.0	2.52	11.20	0.441	44.0	1.73	18.40	0.72	1.75	0.79
2"	50	3000	76.0	2.99	12.70	0.500	48.0	1.89	19.20	0.76	2.46	1.12